WS4A005120A

V_{RRM} = 1200 V

Silicon Carbide Schottky Diode

Typical Performance



Figure 3. Power Dera F8P16.9(b)10.9T



Package

Notes

1) Before using our products, please contact our marketing managers and get the latest specifications.

2) Ongoing efforts are being made to improve the reliability and quality of the products by CETC, but the semiconductors can malfunction due to various factors. Therefore, in order to prevent artificial damage or fire arising from failure, please take safety measures such as complying with the derating characteristics, implementing redundant and fire prevention designs, and utilizing backups and fail-safe procedures. CETC doesn't have responsibility for any damages arising from the use of our products beyond the rating specified by CETC.

3) All the information contained in this document, such as the examples of application circuits, circuit constants, is provided only to illustrate the stand (en (i)12.6 (ded o)38)15.3 (sve s)10ic 3..oerations of the products. The other relevant conditions mus into consideration when designing circuits for mass production.

4) The information specified in this document is intended only to show the typid functions and exples of applicion

ciron reiplp2 (or)3.7 (m)umlc 0 (ent)2y0.6 (do).7 (p24.7 Co60524)13.27.78eo>n d in13.4 (x)ded ons it.4 (x)ded o63m re (i)-0.7y

ADD: No.166 Zhengfang Middle Road, Jiangning District, Nanjing, Jiangsu Province
Email: sic@cetc.com.cn
TEL 025-68005869

CETC All rights reserved.